

HCA65S20D1Q

SiC Silicon Carbide Schottky Diode

650V, 20A

Description

The 650V SiC is an advanced Power Master Semiconductor's silicon carbide diode family. This technology combines the benefits of excellent low capacitive charge and robustness. Consequently, the SiC family is suitable for application requiring high power efficiency.



Applications

- Power Factor Correction
- Industrial Power Supplies
- Solar Inverter, UPS

Features

V_{RRM}	I_F	$T_{J,max}$	Q_C
650 V	20 A	175 °C	62 nC

- No reverse recovery current
- Low capacitive charge
- 175°C Max junction temperature
- High surge current capability
- Switching behavior independent of temperature
- Pb-Free, Halogen Free and RoHS compliant



Absolute Maximum Ratings ($T_C = 25^{\circ}\text{C}$ unless otherwise noted)

Symbol	Parameter		Value	Unit
V_{RRM}	Repetitive Peak Reverse Voltage		650	V
I_F	Forward Current	$T_C=128^{\circ}\text{C}$	20	A
$I_{F,SM}$	Non-Repetitive Forward Surge Current	$T_C=25^{\circ}\text{C}, t_p=10\text{ ms}$	95	A
		$T_C=150^{\circ}\text{C}, t_p=10\text{ ms}$	80.8	A
$I_{F,Max}$	Non-Repetitive Peak Forward Current	$T_C=25^{\circ}\text{C}, t_p=10\text{ us}$	880	A
		$T_C=150^{\circ}\text{C}, t_p=10\text{ us}$	748	A
$I^2dt\text{ value}$	$\int i^2 dt$	$T_C=25^{\circ}\text{C}, t_p=10\text{ ms}$	45.1	A^2s
		$T_C=150^{\circ}\text{C}, t_p=10\text{ ms}$	32.6	A^2s
P_{tot}	Power Dissipation	$T_C=25^{\circ}\text{C}$	121	W
T_J, T_{STG}	Operating Junction and Storage Temperature		-55 to +175	$^{\circ}\text{C}$

Thermal Characteristics

Symbol	Parameter	Value	Unit
$R_{\theta JC}$	Thermal Resistance, Junction to Case, Max.	1.24	$^{\circ}\text{C/W}$

Package Marking and Ordering Information

Part Number	Top Marking	Package	Packing Method	Quantity
HCA65S20D1Q	HCA65S20D1Q	TO-247-2L	Tube	30 units

Electrical Characteristics (T_C = 25°C unless otherwise noted)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
V _F	Forward Voltage	I _F =20 A, T _C =25°C		1.40	1.7	V
		I _F =20 A, T _C =175°C		1.55	-	
I _R	Reverse Current	V _R =650 V, T _C =25°C		-	100	μA
		V _R =650 V, T _C =175°C		-	300	
Q _C	Total Capacitive Charge	V _R =400 V, T _C =25°C		62		nC
C	Total Capacitance	V _R =1 V, f=100 kHz		1010		pF
		V _R =400 V, f=100 kHz		99		
E _C	Capacitance Stored Energy	V _R =400 V, T _C =25°C		9.2		μJ

Typical Performance Characteristics

Figure 1. Power Derating




Figure 2. Current Derating




Figure 3. Forward Characteristics




Figure 4. Reverse Characteristics




Figure 5. Capacitive Charge Characteristic





Figure 6. Capacitance Stored Energy



Typical Performance Characteristics

Figure 7. Capacitance Characteristic






Figure 8. Transient Thermal Response Curve



Package Outlines

TO-247-2L



SYMBOL	MIN	MAX
A	4.80	5.20
A1	2.29	2.54
A2	1.90	2.10
b	1.10	1.30
b1	1.91	2.20
c	0.50	0.70
D	20.80	21.34
D1	17.43	17.83
E	15.75	16.13
E1	13.06	13.46
E2	4.32	4.83
e	10.90 BSC	
L	19.85	20.25
L1	-	4.49
ϕP	3.55	3.65
Q	5.59	6.19
S	6.15 BSC	

* Dimensions in millimeters