

HCB120S20D1

SiC Silicon Carbide Schottky Diode

1200V, 20A

Description

The 1200V SiC is an advanced Power Master Semiconductor's silicon carbide diode family. This technology combines the benefits of excellent low forward voltage and robustness. Consequently, the SiC family is suitable for application requiring high power efficiency.



Applications

- Solar inverter, UPS
- EV charging station
- Power Factor Correction

Features

V_{RRM}	I_F	$T_{J,max}$	Q_C
1200 V	20 A	175 °C	121 nC

- No reverse recovery current
- Low forward voltage
- 175°C Max junction temperature
- High surge current capability
- Switching behavior independent of temperature
- Pb-Free, Halogen Free and RoHS compliant



Absolute Maximum Ratings ($T_C = 25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter		Value	Unit
V_{RRM}	Repetitive Peak Reverse Voltage		1200	V
I_F	Forward Current	$T_C=155^\circ\text{C}$	20	A
$I_{F,SM}$	Non-Repetitive Forward Surge Current	$T_C=25^\circ\text{C}, t_p=10\text{ms}$	135	A
		$T_C=150^\circ\text{C}, t_p=10\text{ms}$	115	A
$I_{F,Max}$	Non-Repetitive Peak Forward Current	$T_C=25^\circ\text{C}, t_p=10\mu\text{s}$	1180	A
		$T_C=150^\circ\text{C}, t_p=10\mu\text{s}$	980	A
I^2dt value	$\int I^2 dt$	$T_C=25^\circ\text{C}, t_p=10\text{ms}$	91	A^2s
		$T_C=150^\circ\text{C}, t_p=10\text{ms}$	66	A^2s
P_{tot}	Power Dissipation	$T_C=25^\circ\text{C}$	333	W
T_J, T_{STG}	Operating Junction and Storage Temperature		-55 to +175	$^\circ\text{C}$

Thermal Characteristics

Symbol	Parameter	Value	Unit
$R_{\theta JC}$	Thermal Resistance, Junction to Case, Max.	0.45	$^\circ\text{C/W}$







Package Marking and Ordering Information

Part Number	Top Marking	Package	Packing Method	Quantity
HCB120S20D1	HCB120S20D1	TO-263	Tape & Reel	2500 units

Electrical Characteristics (T_C = 25°C unless otherwise noted)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
V _F	Forward Voltage	I _F =20A, T _C =25°C		1.39	1.70	V
		I _F =20A, T _C =175°C		1.8	-	
I _R	Reverse Current	V _R =1200V, T _C =25°C		-	100	μA
		V _R =1200V, T _C =175°C		-	300	
Q _C	Total Capacitive Charge	V _R =800V, T _C =25°C		121		nC
C	Total Capacitance	V _R =1V, f=100Khz		1357		pF
		V _R =800V, f=100Khz		85		
E _C	Capacitance Stored Energy	V _R =800V, T _C =25°C		34		μJ

Typical Performance Characteristics



Typical Performance Characteristics

Figure 7. Capacitance Characteristic






Figure 8. Transient Thermal Response Curve



Package Outlines
 TO-263-2L



SYMBOL	MIN	NOM	MAX
A	4.30	4.50	4.70
A1(▼)	0.00	—	0.25
b	0.70	0.80	0.90
b1	1.17	1.27	1.37
c	0.45	0.50	0.60
c1	1.25	1.30	1.40
D	9.00	9.20	9.40
D1	6.50	6.70	6.90
E	9.80	10.00	10.20
E1	7.80	8.00	8.20
E2	9.70	9.90	10.10
e	2.54 BSC		
H	15.00	15.30	15.60
L	2.00	2.30	2.60
L1	1.00	1.20	1.40
L3	0.254 BSC		
θ1	(3°)		

* Dimensions in millimeters