

HCZ120N16M2

N-Channel SiC Silicon Carbide Power MOSFET

1200 V, 118 A, 16 mΩ

Features

- High switching speed with a low gate charge
- Fast intrinsic diode with low reverse recovery
- Robust Avalanche Capability
- 100% Avalanche Tested
- Pb-free, Halogen Free, and RoHS Compliant


Benefits

- System efficiency improvement
- Higher frequency applicability
- Increased power density
- Reduced cooling effort

Applications

- Solar inverter
- EV charging station
- UPS
- Industrial power supply

$BV_{DSS, Tc=25^{\circ}C}$	$I_D, Tc=25^{\circ}C$	$R_{DS(on),typ}$	$Q_{g,typ}$
1200 V	118 A	16 mΩ	152 nC



Absolute Maximum Ratings ($T_C = 25^{\circ}C$ unless otherwise noted)

Symbol	Parameter		Value	Unit
V_{DSS}	Drain to Source Voltage		1200	V
V_{GS}	Gate to Source Voltage (DC)		-10 / +22	V
V_{GSop}	Recommended Operation Value		-5...-3 / +18	V
I_D	Drain Current	Continuous ($T_C = 25^{\circ}C$)	118	A
		Continuous ($T_C = 100^{\circ}C$)	84	
I_{DM}	Drain Current	Pulsed (Note1)	295	A
P_D	Power Dissipation	($T_C = 25^{\circ}C$)	500	W
		Derate Above 25°C	3.3	W/°C
T_J, T_{STG}	Operating and Storage Temperature Range		-55 to 175	°C
T_L	Maximum Lead Temperature for Soldering, 1/8" from Case for 10 Seconds		260	°C

Thermal Characteristics

Symbol	Parameter	Value	Unit
$R_{\theta JC}$	Thermal Resistance, Junction to Case, Max.	0.30	°C/W
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient, Max.	40	

Package Marking and Ordering Information

Part Number	Top Marking	Package	Packing Method	Quantity
HCZ120N16M2	HCZ120N16M2	TO-247-4L	Tube	30 units

Electrical Characteristics ($T_C = 25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
--------	-----------	-----------------	-----	-----	-----	------

Off Characteristics

BV_{DSS}	Drain to Source Breakdown Voltage	$V_{GS} = 0\text{ V}, I_D = 1\text{ mA}$	1200			V
I_{DSS}	Zero Gate Voltage Drain Current	$V_{DS} = 1200\text{ V}, V_{GS} = 0\text{ V}$		1	100	μA
		$V_{DS} = 1200\text{ V}, V_{GS} = 0\text{ V}, T_J = 175^\circ\text{C}$		10		
I_{GSS}	Gate-Source Leakage Current	$V_{GS} = +22\text{ V}, V_{DS} = 0\text{ V}$			+100	nA
		$V_{GS} = -10\text{ V}, V_{DS} = 0\text{ V}$			-100	

On Characteristics

$V_{GS(th)}$	Gate Threshold Voltage	$V_{GS} = V_{DS}, I_D = 24\text{ mA}$ (tested after $V_{GS} = 22\text{ V}, 1\text{ ms pulse}$)	2.0	3.0	4.5	V
$R_{DS(on)}$	Static Drain to Source On Resistance	$V_{GS} = 18\text{ V}, I_D = 50\text{ A}$		16.0	22.4	$\text{m}\Omega$
		$V_{GS} = 18\text{ V}, I_D = 50\text{ A}, T_J = 175^\circ\text{C}$		25.6		
		$V_{GS} = 15\text{ V}, I_D = 50\text{ A}$		21.5		
g_{fs}	Transconductance	$V_{DS} = 20\text{ V}, I_D = 50\text{ A}$		32.7		S

Dynamic Characteristics

C_{iss}	Input Capacitance	$V_{DS} = 800\text{ V}, V_{GS} = 0\text{ V}, f = 250\text{ kHz}$		4063		pF
C_{oss}	Output Capacitance			227		
C_{rss}	Reverse Capacitance			3		
E_{oss}	Stored Energy in Output Capacitance	$V_{DS} = 0\text{ V to } 800\text{ V}, V_{GS} = 0\text{ V}$		94		μJ
$C_{o(er)}$	Energy Related Output Capacitance			295		pF
$C_{o(tr)}$	Time Related Output Capacitance			476		
$Q_{g(tot)}$	Total Gate Charge	$V_{DS} = 800\text{ V}, I_D = 50\text{ A},$ $V_{GS} = -3\text{ V} / 18\text{ V},$ Inductive load		152		nC
Q_{gs}	Gate to Source Charge			49		
Q_{gd}	Gate to Drain "Miller" Charge			29		
R_G	Internal Gate Resistance	$f = 1\text{ MHz}, V_{AC} = 30\text{ mV}$		2.7		Ω

Switching Characteristics







$t_{d(on)}$	Turn-On Delay Time	$V_{DS} = 800\text{ V}, I_D = 50\text{ A},$ $V_{GS} = -3\text{ V} / 18\text{ V}, R_G = 4.7\text{ }\Omega,$ FWD : HCH120S20D1, Inductive load		32		ns
t_r	Turn-On Rise Time			25		
$t_{d(off)}$	Turn-Off Delay Time			65		
t_f	Turn-Off Fall Time			11		
E_{on}	Turn-on Switching Energy			539		μJ
E_{off}	Turn-off Switching Energy			302		
E_{tot}	Total Switching Energy			841		

Electrical Characteristics (T_C = 25°C unless otherwise noted)







Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
Source-Drain Diode Characteristics						
I _S	Continuous Diode Forward Current	V _{GS} = -3 V			105	A
I _{SM}	Pulsed Diode Forward Current	V _{GS} = -3 V (Note1)			295	
V _{SD}	Diode Forward Voltage	V _{GS} = -3 V, I _{SD} = 50 A		4.0		V
t _{rr}	Reverse Recovery Time	V _{DD} = 800 V, I _{SD} = 50 A, dI _F /dt = 3000 A/μs, Includes Q _{oss}		22		ns
Q _{rr}	Reverse Recovery Charge			486		nC
I _{rrm}	Peak Reverse Recovery Current			37		A

※Note 1 : Limited by maximum junction temperature.


Typical Performance Characteristics



Typical Performance Characteristics



Typical Performance Characteristics



Typical Performance Characteristics

Figure 19. Maximum Safe Operating Area




Figure 20. Transient Thermal Response Curve




Figure 21. Inductive Load Switching Test Circuit and Waveforms






Figure 22. Peak Diode Recovery dv/dt Test Circuit and Waveforms



Package Outlines

TO-247-4L



SYMBOL	Common		
	DIMENSIONS MILLIMETER		
	MIN.	NOM.	MAX.
A	4.80	5.00	5.20
A1	2.29	2.42	2.54
A2	1.90	2.00	2.10
b	1.10	1.20	1.30
b1	1.86	2.01	2.15
c	0.50	0.60	0.70
D	20.90	21.00	21.10
D1	17.43	17.63	17.83
E	15.75	15.94	16.13
E1	13.46	13.66	13.86
E2	4.32	4.58	4.83
e	2.54 BSC.		
e1	5.08 BSC.		
L	19.80	19.95	20.10
L1	-	-	4.30
P	3.56	3.61	3.66
P1	6.75	6.80	6.85
Q	5.38	5.79	6.20
S	6.15 BSC.		

* Dimensions in millimeters