

# HMP60N120E7

## N-Channel MOS E7 Power MOSFET

600 V, 27 A, 120 mΩ

### Description

The 600V MOS E7 is an advanced Power Master Semiconductor's Super Junction MOSFET family by utilizing charge balance technology for excellent low on-resistance and gate charge.

This technology combines the benefits of a fast switching performance with ease of usage and robustness.

Consequently, the MOS E7 family is suitable for application requiring high power density and superior efficiency.


### Features

$BV_{DSS} @ T_{J,max}$	$I_D$	$R_{DS(on),max}$	$Q_{g,typ}$
650 V	27 A	120 mΩ	43.6 nC

- Reduced Switching & Conduction Losses
- Lower Gate Resistance
- 100% Avalanche Tested
- Pb-free, Halogen Free, and RoHS Compliant

### Applications

- PFC, Hard & Soft Switching Topologies
- Industrial & Consumer Power Supplies



### Absolute Maximum Ratings ( $T_C = 25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Value	Unit
$V_{DSS}$	Drain to Source Voltage	600	V
$V_{GSS}$	Gate to Source Voltage	$\pm 30$	V
$I_D$	Drain Current	Continuous ( $T_C = 25^\circ\text{C}$ )	27
		Continuous ( $T_C = 100^\circ\text{C}$ )	17.3
$I_{DM}$	Drain Current	Pulsed (Note1)	81
$E_{AS}$	Single Pulsed Avalanche Energy	(Note2)	164
$I_{AS}$	Avalanche Current	(Note2)	5.1
$E_{AR}$	Repetitive Avalanche Energy	(Note1)	2.23
dv/dt	MOSFET dv/dt	100	V/ns
	Peak Diode Recovery dv/dt	(Note3)	
$P_D$	Power Dissipation	( $T_C = 25^\circ\text{C}$ )	223
		Derate Above $25^\circ\text{C}$	1.79
$T_J, T_{STG}$	Operating and Storage Temperature Range	-55 to 150	$^\circ\text{C}$
$T_L$	Maximum Lead Temperature for Soldering, 1/8" from Case for 10 Seconds	260	$^\circ\text{C}$

### Thermal Characteristics

Symbol	Parameter	Value	Unit
$R_{\theta JC}$	Thermal Resistance, Junction to Case, Max.	0.56	$^\circ\text{C/W}$
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient, Max.	62.5	

## Package Marking and Ordering Information

Part Number	Top Marking	Package	Packing Method	Quantity
HMP60N120E7	HMP60N120E7	TO-220	Tube	50 units

Electrical Characteristics ( $T_C = 25^\circ\text{C}$  unless otherwise noted)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
--------	-----------	-----------------	-----	-----	-----	------

## Off Characteristics

$BV_{DSS}$	Drain to Source Breakdown Voltage	$V_{GS} = 0\text{ V}, I_D = 1\text{ mA}$	600			V
		$V_{GS} = 0\text{ V}, I_D = 1\text{ mA}, T_J = 150^\circ\text{C}$	650			
$I_{DSS}$	Zero Gate Voltage Drain Current	$V_{DS} = 600\text{ V}, V_{GS} = 0\text{ V}$			1	$\mu\text{A}$
		$V_{DS} = 480\text{ V}, V_{GS} = 0\text{ V}, T_J = 125^\circ\text{C}$		2		
$I_{GSS}$	Gate-Source Leakage Current	$V_{GS} = \pm 30\text{ V}, V_{DS} = 0\text{ V}$			$\pm 100$	nA

## On Characteristics

$V_{GS(th)}$	Gate Threshold Voltage	$V_{GS} = V_{DS}, I_D = 1.8\text{ mA}$	2.5		4.5	V
$R_{DS(on)}$	Static Drain to Source On Resistance	$V_{GS} = 10\text{ V}, I_D = 12.6\text{ A}$		103	120	m $\Omega$

## Dynamic Characteristics

$C_{iss}$	Input Capacitance	$V_{DS} = 400\text{ V}, V_{GS} = 0\text{ V},$ $f = 250\text{ kHz}$		1827		pF
$C_{oss}$	Output Capacitance			48.9		pF
$C_{o(tr)}$	Time Related Output Capacitance	$V_{DS} = 0\text{ V to } 400\text{ V}, V_{GS} = 0\text{ V}$		500		pF
$C_{o(er)}$	Energy Related Output Capacitance			78		pF
$Q_{g(tot)}$	Total Gate Charge at 10 V	$V_{DS} = 400\text{ V}, I_D = 12.6\text{ A},$ $V_{GS} = 10\text{ V}$		43.6		nC
$Q_{gs}$	Gate to Source Charge			9.6		nC
$Q_{gd}$	Gate to Drain "Miller" Charge			20.2		nC
$R_G$	Gate Resistance	$f = 1\text{ MHz}$		1		$\Omega$

## Switching Characteristics

$t_{d(on)}$	Turn-On Delay Time	$V_{DS} = 400\text{ V}, I_D = 12.6\text{ A},$ $V_{GS} = 10\text{ V}, R_G = 10\ \Omega$ See Figure 13		15		ns
$t_r$	Turn-On Rise Time			9		ns
$t_{d(off)}$	Turn-Off Delay Time			76		ns
$t_f$	Turn-Off Fall Time			10		ns

## Source-Drain Diode Characteristics

$I_S$	Maximum Continuous Diode Forward Current			27		A
$I_{SM}$	Maximum Pulsed Diode Forward Current			81		A
$V_{SD}$	Diode Forward Voltage	$V_{GS} = 0\text{ V}, I_{SD} = 12.6\text{ A}$			1.2	V
$t_{rr}$	Reverse Recovery Time	$V_{DD} = 400\text{ V}, I_{SD} = 12.6\text{ A},$ $di_F/dt = 100\text{ A}/\mu\text{s}$		300		ns
$Q_{rr}$	Reverse Recovery Charge			4.1		$\mu\text{C}$

## ※Notes:

1. Repetitive rating: pulse-width limited by maximum junction temperature.
2.  $I_{AS} = 5.1\text{ A}, R_G = 25\ \Omega$ , starting  $T_J = 25^\circ\text{C}$ .
3.  $I_{SD} \leq 12.6\text{ A}, di/dt \leq 100\text{ A}/\mu\text{s}, V_{DD} \leq 400\text{ V}$ , starting  $T_J = 25^\circ\text{C}$ .

Typical Performance Characteristics

Figure 1. On-Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance Characteristics vs. Drain Current and Gate Voltage




Figure 4. Diode Forward Voltage Characteristics vs. Source-Drain Current and Temperature




Figure 5. Capacitance Characteristics





Figure 6. Gate Charge Characteristics



Typical Performance Characteristics

Figure 7. Breakdown Voltage Characteristics vs. Temperature




Figure 8. On-Resistance Characteristics vs. Temperature




Figure 9. Maximum Safe Operating Area




Figure 10. Maximum Drain Current vs. Case Temperature




Figure 11. E\_oss vs. Drain to Source Voltage





Figure 12. Transient Thermal Response Curve



Test Circuits

Figure 13. Inductive Load Switching Test Circuit and Waveforms




Figure 14. Unclamped Inductive Switching Test Circuit and Waveforms







Figure 15. Peak Diode Recovery  $dv/dt$  Test Circuit and Waveforms



Package Outlines

TO-220



SYMBOL	MIN	NOM	MAX
A	4,30	4,50	4,70
A1	1,25	1,30	1,40
A2	2,20	2,40	2,60
b	0,70	0,80	0,90
b1	1,42	1,52	1,62
b2	1,17	1,27	1,37
c	0,45	0,50	0,60
D	15,50	15,70	15,90
D1	9,00	9,20	9,40
D2	13,10	13,30	13,50
E	9,70	9,90	10,10
E1	(8,80)		
E2	(0,60)		
E3	9,80	10,00	10,20
e	2,54 BSC		
e1	5,08 BSC		
H1	6,30	6,50	6,70
L	12,88	13,08	13,28
L1	(3,00)		
$\phi P$	3,40	3,60	3,80
Q	2,70	2,80	2,90

\* Dimensions in millimeters